



ULC Standards
Normes ULC



ANSI/CAN/UL/ULC 567B:2024

JOINT CANADA – UNITED
STATES NATIONAL STANDARD

STANDARD FOR SAFETY

Emergency Breakaway Fittings, Swivel Connectors and Pipe-Connection Fittings for Diesel Fuel, Biodiesel Fuel, Diesel/Biodiesel Blends with Nominal Biodiesel Concentrations up to 20 Percent (B20), Kerosene, and Fuel Oil



ANSI/UL 567B-2024



SCC FOREWORD

National Standard of Canada

A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at www.scc.ca.

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada's economic competitiveness and social well-being, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at www.scc.ca.

ULNORM.COM : Click to view the full PDF of UL 567B 2024

UL Standard for Safety for Emergency Breakaway Fittings, Swivel Connectors and Pipe-Connection Fittings for Diesel Fuel, Biodiesel Fuel, Diesel/Biodiesel Blends with Nominal Biodiesel Concentrations up to 20 Percent (B20), Kerosene, and Fuel Oil, ANSI/CAN/UL/ULC 567B

Second Edition, Dated May 31, 2024

Summary of Topics

This new Second Edition of ANSI/CAN/UL/ULC 567B dated May 31, 2024 is being issued as a new joint US/Canada Standard reflecting the latest ANSI and SCC approval dates and incorporating the proposal dated August 4, 2023.

The new requirements are substantially in accordance with Proposal(s) on this subject dated August 4, 2023.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

[ULNORM.COM](https://ulnorm.com) : Click to view the full PDF of UL 567B 2024



ANSI/UL 567B-2024

MAY 31, 2024



1

ANSI/CAN/UL/ULC 567B:2024

**Standard for Emergency Breakaway Fittings, Swivel Connectors and Pipe-
Connection Fittings for Diesel Fuel, Biodiesel Fuel, Diesel/Biodiesel Blends
with Nominal Biodiesel Concentrations up to 20 Percent (B20), Kerosene,
and Fuel Oil**

Prior to the first edition, the requirements for the products covered by this standard were included in the Outline of Investigation for Emergency Breakaway Fittings, Swivel Connectors and Pipe-Connection Fittings for Diesel Fuel, Biodiesel Fuel, Diesel/Biodiesel Blends with Nominal Biodiesel Concentrations up to 20 Percent (B20), Kerosene, and Fuel Oil, UL 567B.

First Edition – March, 2015

Second Edition

May 31, 2024

This ANSI/CAN/UL/ULC Safety Standard consists of the Second Edition.

The most recent designation of ANSI/UL 567B as an American National Standard (ANSI) occurred on May 31, 2024. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page, Preface or SCC Foreword.

This Standard has been designated as a National Standard of Canada (NSC) on May 31, 2024.

COPYRIGHT © 2024 ULSE INC.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 567B 2024

CONTENTS

Preface	5
----------------------	----------

INTRODUCTION

1 Scope	7
2 Components	8
3 Units of Measurement	8
4 Referenced Publications	8
5 Glossary.....	9

CONSTRUCTION

6 General	10
7 Materials	10
7.1 Metallic materials.....	10
7.2 Nonmetallic materials.....	11
7.3 Casting impregnation materials.....	13
7.4 Internal parts	14
8 Swivel Connectors and Emergency Breakaway Fittings	14
9 Pipe-Connecting Fittings.....	14
10 End Connections.....	15

PERFORMANCE

11 General	18
12 Long Term Exposure Test	19
12.1 General.....	19
12.2 Samples	19
12.3 Method	20
12.4 Results	21
13 Electrical-Continuity Test.....	21
13.1 General.....	21
13.2 Electrical continuity measurement.....	21
13.3 Electrical continuity alternate method	21
14 External Leakage Test	22
15 Seat Leakage Test.....	22
16 Operation Test	22
17 Endurance Test.....	26
18 Abuse Test.....	26
19 Drop Test.....	27
20 Hydrostatic Strength Test.....	27
21 Pull Test.....	28
21.1 Pipe-connecting fitting.....	28
21.2 Emergency breakaway fitting.....	28
22 Marking Adhesion Test	29
23 Moist Ammonia-Air Stress Cracking Test.....	29

MANUFACTURING AND PRODUCTION

24 General	30
------------------	----